

DALI Driver for LED Linear 1500mm

- Power factor >0.9
- Tridonic LED DALI Driver for 1500mm LED Linear
- Code: LCA 45W 500–1400mA one4all SC PRE
- Power Factor $\geq 0,9$
- DALI dimmable
- DSI
- switchDIM and corridorFunction



Order Code	52931
General Data	
Primary Voltage Range (V)	200-240
Operating Frequency (Hz)	50-60
Input Current (A)	0.132 - 0.224
Output Current (A)	0.50 - 1.40
Secondary Voltage (V)	50V max (depending on selected current)
Power Factor	0.98
Ambient Temperature t_a (°C)	-25 to 50
Max Case Temperature t_c (°C)	85
Dimming	DALI
Dimensions LxWxH (mm)	150 x 43 x 30
Protection Class	IP20
Weight (g)	145
Primary Terminal	3-pole, pre-wired with dedicated connector
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN 60347-1
	EN 60347-2-13
	EN 55015
	EN 61000-3-2
	EN 61000-3-3
	EN 61547
	EN62384
	EN62384-101/- 102/-207

Specifications are subject to operating with halogen lamps



DALI Driver for LED Linear 1500mm

Order Code	52931
Product Description	Tridonic LED DALI Driver for 1500mm LED Linear

Technical Packaging Details

Barcode	23942529316
Outer EAN 14	50023942529311
Inner EAN 128	(02)00023942529316(37)40(91)52
Pack Dimensions (HxWxL)	46mm x 75mm x 215mm
Pack Weight (g)	170
Carton Qty (Shipping Unit)	1
Layers/Pallet	3
Units/Pallet	600