

Verbatim LED Driver for 30W Recessed Downlight

- Power factor >0.9
- Flicker-free

Order Code	52942
General Data	
Primary Voltage Range (V)	200-240
Operating Frequency (Hz)	50-60
Input Current (A)	0.14
Output Current (A)	0.77
Secondary Voltage (V)	30-42
Input Wattage (W)	30 (with Verbatim LED "Trumpet" and Indirect Downlights)
Power Factor	>0.9
Ambient Temperature t_a (°C)	-10 to 50
Max Case Temperature t_c (°C)	65
Dimensions LxWxH (mm)	134x48x29
Weight (g)	120
Primary Terminal	No wire
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN 60347-1
	EN 60347-2-13
	EN 55015
	EN 61000-3-2
	EN 61000-3-3
	EN 61547

Specifications are subject to operating with halogen lamps



Verbatim LED Driver for 30W Recessed Downlight

Order Code 52942

Product Description Verbatim LED Driver for 30W Recessed Downlight

Technical Packaging Details

Barcode	23942529422
Outer EAN 14	50023942529427
Inner EAN 128	(02)00023942529422(37)10(91)814
Pack Dimensions (HxWxL)	45mm x 50mm x 155mm
Pack Weight (g)	185
Carton Qty (Shipping Unit)	1
Cartons/pallet	135
Layers/Pallet	5
Units/Pallet	1350