

Verbatim LED Driver for 15W Recessed Downlight

- Power factor >0.9
- Flicker-free



Order Code	52946
General Data	
Primary Voltage Range (V)	200-240
Operating Frequency (Hz)	50-60
Input Current (A)	0.068
Output Current (A)	0.0365
Secondary Voltage (V)	30-42
Input Wattage (W)	15 (with Verbatim LED "Trumpet" and Indirect Downlights)
Power Factor	>0.9
Ambient Temperature t_a (°C)	-10 to 50
Max Case Temperature t_c (°C)	80
Dimensions LxWxH (mm)	121.5x43.5x25.5
Weight (g)	95
Primary Terminal	No wire
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN 60347-1
	EN 60347-2-13
	EN 55015
	EN 61000-3-2
	EN 61000-3-3
	EN 61547

Specifications are subject to operating with halogen lamps



Created October 2018

www.verbatimlighting.com

Verbatim LED Driver for 15W Recessed Downlight

Order Code	52946
Product Description	Verbatim LED Driver for 15W Recessed Downlight

Technical Packaging Details

Barcode	23942529460
Outer EAN 14	50023942529465
Inner EAN 128	(02)00023942529460(37)1091814
Pack Dimensions (HxWxL)	35mm x 60mm x 130mm
Pack Weight (g)	109
Carton Qty (Shipping Unit)	1
Cartons/pallet	174
Layers/Pallet	6
Units/Pallet	1740