

DALI Driver for LED Linear 600mm

- Tridonic LED DALI Driver for 600mm LED Linear
- Code: LCA 25W 350-1050mA one4all SC PRE
- Power Factor * 0,9
- DALI dimmable
- DSI
- switchDIM and corridorFunction



Order Code	52976
General Data	
Primary Voltage Range (V)	200-240
Operating Frequency (Hz)	50-60
Input Current (A)	0.058 - 0.071
Output Current (A)	0.275 (Adjusted by ready2mains)
Secondary Voltage (V)	54V max (depending on selected current)
Power Factor	0.85
Ambient Temperature t_a (°C)	-25 to 65
Max Case Temperature t_c (°C)	80
Dimming	DALI
Dimensions LxWxH (mm)	280 x 30 x 21
Weight (g)	180
Lifetime	100,000h (at T_a 65degreeC)
Primary Terminal	3-pole, pre-wired with dedicated connector
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN 60347-1
	EN 60347-2-13
	EN 55015
	EN 61000-3-2
	EN 61000-3-3
	EN 61547
	EN62384
	EN62384-101/-102/-207

Specifications are subject to operating with halogen lamps



DALI Driver for LED Linear 600mm

Order Code	52976
Product Description	Tridonic LED DALI Driver for 600mm LED Linear

Technical Packaging Details

Barcode	23942529767
Outer EAN 14	50023942529762
Inner EAN 128	(02)00023942529767(37)50(91)52
Pack Dimensions (HxWxL)	26mm x 33mm x 285mm
Pack Weight (g)	230
Carton Qty (Shipping Unit)	1
Layers/Pallet	4
Units/Pallet	1600